



Appalachian Birch



■ Smoky Mountain Pine



■ Shenandoah Oak



■ Cambridge Walnut



■ Lexington Pecan



■ Appalachian Birch



■ Springfield Birch



■ Portsmouth Oak



■ Cumberland Cedar



■ Concord Oak



■ Charleston Oak



■ Rubra Elm



■ Chatham Walnut



■ Pumilla Elm



■ Arcadian Oak



■ Chaminade Oak

Features

- Length: ■ 36"
 ■ 48"
- Width: 6"
- Thickness: 2mm
 12mil wear layer
- Finish: Surface Guardian UV Coating
- Edge Detail: Square
- FloorScore® Certified: Registration # SCS-FS-03695
- Warranty: 25 year Residential Finish & Lifetime Residential
 ■ 5 years Commercial Finish (6" x 36") and 10 year Commercial Structural
 OR
 ■ 7 years Commercial Finish (6" x 48") and 10 year Commercial Structural
- Maintenance: Clean with TrueClean Floor Cleaner.
 For full care and maintenance instructions visit
 HallmarkFloors.com/Floor-Care-Maintenance

Benefits

- Fashion: Natural Low Sheen
 Embossed Wood Texture
 Fashionable Widths & Lengths
- Performance: Waterproof
 Anti Bacterial & Fungal Control
 100% Renewable with Hallmark's ABC Recoat System
 PureCore Ultra- 100% Pure Virgin Vinyl
- Clean Air: Formaldehyde Free & Ortho Phthalate Free
 Safer Indoor Environment for Children
 100% FloorScore Certified

Installation



Double Glue with Eternity LVT underlayment system or equivalent.



Refer to www.hallmarkfloors.com for latest, updated information.



ASTM Testing

Flexibility	Pass	ASTM F137
Thickness Standard	Pass	ASTM F386
Resistance to Chemicals (5 min.)	Pass	ASTM F925 5
Resistance to Chemicals (24 hr.)	Pass	ASTM F925
Stain Resistance	Pass	ASTM F925
Heat Stability by Color Change	Pass	ASTM F1514
Light Stability by Color Change	Pass	ASTM F1515
Dimensional Stability after exposure to heat	Pass	ASTM F219
Fire Resistance	Class C - Pass	ASTM E 648
Coefficient of Friction	Pass	ASTM D2047-04
Static Load	Pass	ASTM F970-07
Stain Resistance	Pass	ASTM F925
Short Term Indentation	Pass	ASTM F1914-98
Smoke Density	Pass	ASTM E662-09
Wear Resistance	High	ASTM F510-93
Formaldehyde Emission (air)	None Detected	EN 7171-1

ISO 14001 Certified Environmental Management System



Certified FloorScore: Independent 3rd Party IAQ verification system for low emitting flooring. Approved as CHPS 01350 compliant and recognized in LEED EQ Credit 4.3