



Collections: Times Square Commercial Flooring | Commercial Waterproof Flooring

Commercial Moderate: EN 31 - Bedrooms, Hotels, Conference Rooms Small Offices

Commercial General: EN 32 - Classrooms, Small Offices, Hotels Boutiques

Dimensions: 6" x 48" Plank (Duomo Stone & Wood End Grain) OR 18" x 36" Tile (Stone/Lineal Concrete & Fabric)

Thickness: 5.5mm

Wear Layer: 20Mil (.5mm)

Length: Random up to 6'2"

Edge: Bevel (Duomo Stone & Wood End Grain) OR Square (Stone/Lineal Concrete & Fabric)

Surface Texture: Various

Finsh: Surface Guardian Pro UV Coating

Package: 36 sqft / carton; 48 cartons / pallet

Weight: 37.16 lbs / carton (6" x 48") OR 38.13 lbs / carton (18" x 36")

Warranty: 10 years commercial Finish and 20 year commercial structural

FloorScore® Certificate: [Registration # SCS-FS-04192](#)

Installation Options: Glue Down

Flexibility (ASTM F137): Pass

Thickness Standard (ASTM F386) Pass

Resistance to Chemicals (5 minute standard) (ASTM F925 5): Pass

Resistance to Chemicals (24 hour standard) (ASTM F925): Pass

ASTM F925 - Stain Resistance: Pass

Heat Stability by Color Change (ASTM F1514): Pass

Light Stability by Color Change (ASTM F1515): Pass

Short Term Indentation (ASTM F1914-98): Pass

Dimensional Stability after exposure to heat (ASTM F2199): Pass

Fire Resistance (ASTM E648): Class 1 - Pass

Coefficient of Friction (ASTM D-2047-04): Exceeds ADA Guidelines of .60

Smoke Density (ASTM E662-09): Pass

Static Load (ASTM F970-07): Pass

Wear Resistance (ASTM F510-93): Pass

Formaldehyde Emission (Air): None Detected – E1 Rating* E1 Standard not to exceed 0.124 mg/ m3 air Method Detection Limit 0.080 mg/ m3 air

Impact Insulation Class IIC (ASTM E-492, E-989): Eternity Underlayment IIC 71/ Delta 21