



FOR NON-POROUS  
SUBSTRATES

# Sika® Level-02 EZ Primer

## ACRYLIC PRIMER FOR NON ABSORBENT SUBSTRATES

- One component
- Excellent primer for difficult substrates
- Ideal on epoxy, ceramic tiles, old vinyl, linoleum, rubber and other coverings
- Compatible with Sika® Level products

Available in  
1 gal.pail



BUILDING TRUST



# Sika® Level-02 EZ Primer

## ACRYLIC PRIMER FOR NON ABSORBENT SUBSTRATES

### WHERE TO USE

- Interior only
- Terrazzo, ceramic tiles, natural stone
- Old substrates with water-resistant adhesive residues
- Fully-bonded old elastic coverings
- Old sealed / coated substrates

**NOTE:** Always refer to current PDS and SDS for detailed performance specifications prior to use.





















### TYPICAL DATA (Material and curing conditions @ 73°F (23°C) and 50% R.H.)

<b>Color</b>	Mint
<b>Chemistry</b>	Acrylic
<b>Density (ASTM C185)</b>	81 lbs/cu.ft.
<b>Drying Time</b>	1 - 2 hours
<b>Coverage</b>	350 - 500 sq.ft. per 1 gallon

### FEATURES AND BENEFITS

- Provides optimum adhesion
- Ready-to-use, no dilution required
- Quick dry time
- Solvent free
- Suitable for application on subfloor radiant system
- Low consumption of material
- Low VOC

### Sika® Classification Chart

Flow					
Speed					
For Porous					
For Non-Porous					



## FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: [www.sikasecure.com](http://www.sikasecure.com)

**Sika Corporation**  
 201 Polito Avenue  
 Lyndhurst, NJ 07071  
 Phone: 201-933-8800  
 Fax: 201-933-6225



**BUILDING TRUST**

