



# Sika® Level-225

## HIGH FLOW, SELF-LEVELING UNDERLAYMENT

- Superior workability for easy installations
- Apply as low as 1/16" in pedestrian areas
- Strong bond to the substrates

Available in  
55 lb. Bag



BUILDING TRUST



# Sika® Level-225

## HIGH FLOW, SELF-LEVELING UNDERLAYMENT

### WHERE TO USE

- Interior use only
- Levels, flattens, and smooths substrates before application of resilient floor
- Suitable on concrete, ceramic and quarry tile, OSB/Plywood, and well bonded LVT
- Leveling work for residential and commercial projects with normal wear requirements

### FEATURES AND BENEFITS

- High flow
- Very smooth surface
- Install most floor covering in 16 hours
- Pumpable self-leveling
- Zero VOC content and low odor
- 1/16" in pedestrian areas

**NOTE:** Always refer to current PDS and SDS for detailed performance specifications prior to use.

#### TYPICAL DATA (Material and curing conditions @ 73°F (23°C) and 50% R.H.)

Color	Concrete Gray
Application Thickness	1/16" up to 1.5" (3 mm up to 38 mm) Can be extended with aggregate to 2.5" (64 mm)
Density (ASTM C185)	130 lbs/cu.ft.
Working Time	Approx. 25 minutes
Ready for Foot Traffic	2-3 hours
Flexural Strength (ASTM C348)	1,250 psi (8.6 MPa) at 28 days
Compressive Strength (ASTM C109)	4,500 psi (31 MPa) at 28 days
VOC (EPA METHOD 24)	0 g/l

#### Sika® Classification Table

Strength					
Flow					
Depth					
Speed					



## FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: [www.sikasecure.com](http://www.sikasecure.com)

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 201-933-8800  
Fax: 201-933-6225



**BUILDING TRUST**

