



MVER
TOLERABLE



SMOOTH
QUALITY

Sika[®] Level SkimCoat

FAST SETTING, SMOOTHING AND FINISHING COMPOUND

- Levels new and old floors
- Re-workable up to 30 minutes after mixing; No additional water needed
- No MVER (Moisture Vapor Emission Rate) limits
- For Interior use only

Packaging available

10 lb. Bag



BUILDING TRUST



Sika® Level SkimCoat

FAST SETTING, SMOOTHING AND FINISHING COMPOUND

WHERE TO USE

- For Interior use only
- Concrete, wood subfloors, ceramic and quarry tiles
- Minor defects, holes, and cracks in concrete and wood subfloors
- Pre-fill non-moving joints and seams
- Radiant heating systems

FEATURES AND BENEFITS

- Easy to prepare and quick to apply
- True feather edge material
- Zero VOC's
- Levels new and old floors
- Adhesion to substrates, subfloors and stable adhesive residue.
- Rapid Setting
- Excellent standard of finish can be achieved to allow direct application of floor coverings

NOTE: Always refer to current PDS and SDS for detailed performance specifications prior to use.

TYPICAL DATA (Material and curing conditions @ 73°F (23°C) and 50% R.H.)

| | |
|----------------------------------|--|
| Color | Gray |
| Application Thickness | Feather edge - 1/2". (13 mm) |
| Working Time | 10 to 20 min. |
| Set Times | Initial: 20 to 30 min. Final: 30 to 60 min. |
| Compressive Strength (ASTM C109) | 3,700 psi (25 MPa) at 28 days |
| Flexural Strength (ASTM C348) | 1,300 psi (9 MPa) at 28 days |
| Flammability (ASTM E84) | Flame Spread 0; Smoke Development 0 |
| VOC (EPA METHOD 24) | 0 g/l |

Sika® Classification Table

| | | | | | |
|------------|--|--|--|--|--|
| Strength | | | | | |
| Smoothness | | | | | |
| Depth | | | | | |
| Speed | | | | | |



FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.sikasecure.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225



BUILDING TRUST

