

FEATURES

| PRODUCT                              | XCORA® STRAND BAMBOO PANELS & VENEER   |                                     |                    |                                 | PUREFORM™ BAMBOO PANELS & VENEER                              |                                 |                                |                                     |                                |                                |                                |                                |                     |  |
|--------------------------------------|--|-------------------------------------|--------------------|---------------------------------|---|---------------------------------|--------------------------------|-------------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|---------------------|--|
|                                      | 1/42" Solid (.6mm)   | 1/8" Solid (3.3mm)                  | 1/4" Solid (6.4mm) | 3/4" CrossPly (19mm)            | 1/42" Solid (.6mm)  | 1/21" 2-ply (1.2mm)             | 1/8" 5-ply (3.3mm)             | 1/4" Solid (6.4mm)                  | 1/4" CrossPly (6.4mm)          | 1/2" CrossPly (13mm)           | 3/4" Solid (19mm)              | 3/4" CrossPly (19mm)           | 13/16" Solid (21mm) |  |
| Size                                 | 4' x 6' x 1/42"  | 4' x 6' x 1/8"                      | 4' x 6' x 1/4"     | 4' x 6' x 3/4"                  | 4' x 8' x 1/42" Oversized Sheet                               | 4' x 8' x 1/21" Oversized Sheet | 4' x 8' x 1/8" Oversized Sheet | 4' x 8' x 1/4" Oversized Sheet      | 4' x 8' x 1/4" Oversized Sheet | 4' x 8' x 1/2" Oversized Sheet | 4' x 8' x 3/4" Oversized Sheet | 4' x 8' x 3/4" Oversized Sheet | 1' x 8' x 13/16"    |  |
| Construction                         | Single Ply - 25g fiber backing   | Single Ply                          | Solid              | 3 Ply                           | Single Ply - 60g paper fleece backing                         | 2 Ply - No backing              | 5 Ply - No backing             | Solid                               | 3 Ply                          | 3 Ply                          | Solid                          | 3 Ply                          | Solid               |  |
| Adhesive                             | Urea Formaldehyde-Free   |                                     |                    |                                 | Formaldehyde Free   |                                 |                                | Ultra Low Emitting Formaldehyde**   |                                |                                |                                |                                |                     |  |
| Hardness                             | 160% Harder Than Oak   |                                     |                    |                                 | 40% Harder Than Oak   |                                 |                                |                                     |                                |                                |                                |                                |                     |  |
| Colors                               | Brindle, Chestnut & Wheat  | Chestnut & Wheat                    | Chestnut & Wheat   | Brindle, Chestnut, Java & Wheat | FGC, FGN, VGC & VGN   | VGC & VGN                       | VGC & VGN                      | VGC & VGN                           | FGC, FGN, VGC & VGN            | VGC & VGN                      | VGC & VGN                      | FGC, FGN, VGC & VGN            | FGC, FGN, VGC & VGN |  |
| Grade                                | Furniture Grade  |                                     |                    |                                 |   |                                 |                                |                                     |                                |                                |                                |                                |                     |  |
| Grit                                 | Sanded to 120 grit all sides   | Sanded to 180 grit all sides        |                    |                                 | Sanded to 180 grit all sides                                  |                                 |                                |                                     |                                |                                |                                |                                |                     |  |
| Indoor Air Quality Rating            |  | SCS Indoor Advantage Gold certified |                    |                                 | Meets CA 01350 Emissions Requirements - CARB I + II compliant |                                 |                                | SCS Indoor Advantage Gold certified |                                |                                |                                |                                |                     |  |
| FSC Certified                        |  |                                     |                    |                                 | *   | *                               | *                              | *                                   | *                              | *                              | *                              | *                              | *                   |  |
| USDA BioPreferred                    |  | ✓                                   | ✓                  | ✓                               | ✓   | ✓                               | ✓                              | ✓                                   | ✓                              | ✓                              | ✓                              | ✓                              | ✓                   |  |
| LEED® IEQ 4.4 Low Emitting Materials | ✓  | ✓                                   | ✓                  | ✓                               | ✓   | ✓                               | ✓                              |                                     |                                |                                |                                |                                |                     |  |
| LEED® MR6 Rapidly Renewable Resource | ✓  | ✓                                   | ✓                  | ✓                               | ✓   | ✓                               | ✓                              | ✓                                   | ✓                              | ✓                              | ✓                              | ✓                              | ✓                   |  |
| LEED® MR7 Certified Wood             |  |                                     |                    |                                 | *   | *                               | *                              | *                                   | *                              | *                              | *                              | *                              | *                   |  |
| Warranty                             | 5 years from the date of purchase  |                                     |                    |                                 |   |                                 |                                |                                     |                                |                                |                                |                                |                     |  |
| Acclimation                          | Ensure product is maintained at 35-55% relative humidity throughout fabrication and installation |                                     |                    |                                 |   |                                 |                                |                                     |                                |                                |                                |                                |                     |  |

\* Available by special order. Allow 10-12 weeks. \*\*3/4" cross-ply VGC color also available with formaldehyde-free adhesive