



## DURACLEAR MAX

Two-component, water-based clear finish

## Count on DuraClear Max to deliver the ultimate look AND protection.

A GREENGUARD Certified, non-ambering, two-component, urethane/acrylic floor finish specifically made for commercial and high-traffic residential floors. DuraClear Max offers excellent scratch, moisture, chemical and slip resistance, which means it provides a level of durability you can stake your reputation on.

- Formulated for use with Quick Coat stain for a system guarantee
- DURABILITY DURABILITY
- High solids, high-build formula offering the ultimate durability
- Two-component technology for maximum performance in scratch, moisture and chemical resistance
- · Superior flow and leveling making it a breeze to apply
- Six-hour pot life allows for less product waste
- Excellent coverage for better efficiency
- Two-hour recoat interval for faster return to service
- Nonambering clear for a beautiful, finished appearance
- GREENGUARD Certified for low chemical indoor emissions
- Complies with LEEDS criteria for low-emitting materials
- · Easy soap-and-water cleanup

## Get with the system.

DuraSeal® Quick Coat stain and water-based finishes are certified to GREENGUARD standards for low chemical emissions into indoor air.



2 HR

To learn more, visit greenguard.org



Since 1898, generations of contractors have counted on us to deliver the highest-quality wood floor coatings. You know DuraSeal Quick Coat stain as simply the best stain on the market.

And we know there is only one way to best protect your Quick Coat stain — by using premium DuraSeal water-based finishes.

Contact us today for a FREE product demo — visit duraseal-wb.com



SHEEN	PRODUCT#	UPC	SIZE	CASE QTY
Flat	809200000	027426809208	1-Gallon	2
Satin	809100000	027426809109	1-Gallon	2
Semi-Gloss	809050000	027426809055	1-Gallon	2
Gloss	809000000	027426809000	1-Gallon	2

Sand and prepare floor according to NWFA-recommended methods. For preparation and application instructions, please see product data sheet.

Color	Clear		
Odor	Very low, mild amine		
Solids	33% to 36% Crosslinked		
Viscosity	55-100 centipoises		
Coverage	500-600 sq. ft./gallon		
Number of Coats	Two to three		
Pot Life	Six hours		
Leveling	Excellent		
Defoaming	Excellent		
VOC	275 maximum crosslinked		
Coefficient of Friction	≥ 0.5 (Passed)		
Dry Film Thickness	1.4 mil. coat		
Freeze/Thaw Stable	Yes		
Shelf Life	Two years		
Cleanup	Warm water		
Maintenance	DuraSeal Hardwood Floor Cleaner		
Storage	Room temperature		
Working Temperature	Ambient temp between 50 °F and 90 °F, humidity below 80%		
Applicator	Synthetic T-bar, roller or pad		
GREENGUARD Certified	Yes		
Comply with LEEDS Criteria	Yes		
Dry Time (at 77 °F and 50%	relative humidity)		
Recoat	Two hours		
Foot Traffic	24 hours		
Return to Service	72 hours		
Full Cure	One week		
Furniture and Rugs	One week		
Gloss Level (at 60)			
Flat	4 +/- 4		
Satin	17 +/- 5		
Semi-Gloss	40 +/- 5		
Gloss	90 minimum		

